



SMART UF75 extreme short throw beamer

Product Description

The SMART UF75 ultra-short-throw projector offers improved shadow reduction and enhanced brightness, and it's both 3D and HD ready. It has a throw distance of approximately 0.6 m, provides 2,500 lumens in standard mode and projects crisp images with high contrast and color quality. The projector can display both 3D lesson content and high-definition video, and has an HDMI input.

The projector's extended control panel makes it easy for teachers to control other audiovisual devices in the classroom from the front of the interactive whiteboard. With one touch, they can switch between inputs and control power and volume. The projector is mounted directly above the interactive whiteboard for simple installation, and the swivel projector mount makes alignment easy. The UF75 is also energy efficient, consuming less than 1 watt of power in standby mode. And its long-lasting lamp and filter-free design reduce maintenance costs.

The SMART UF75 projector features a filter-free design, enabled by the use of DLP technology. This technology ensures that there are no filters to clean, maintain and replace, thereby reducing your annual maintenance effort and cost.

General

- **Projector type** DLP projector
- **3D** Yes
- **Dimensions (WxDxH)** 14.0 in x 28.0 in x 15.5 in
- **Weight** 17.0 lbs
- **Features** 5:4 aspect ratio support, BrilliantColor, 16:10 aspect ratio support, 16:9 aspect ratio support

Display

- **Image Brightness** 2500.0 ANSI lumens
- **Image Contrast Ratio** 2900:1
- **Resolution** XGA - 1024 x 768
- **Native Aspect Ratio** 4:3

Lens / Optical

- **Lens** Ultra short-throw lens

Video Input

- **Analog Video Format** PAL-N, NTSC, PAL, SECAM, PAL-M, NTSC 4.43
- **Analog Video Signal** S-Video, Composite video, RGB
- **Digital Video Standard** High-Definition Multimedia Interface (HDMI)

Expansion / Connectivity

- **Interfaces** 2.0 x Audio line-out - RCA (Management), 1.0 x Serial RS-232 - Mini-phone 3.5 mm (Management), 1.0 x Network - 15 pin HD D-Sub (HD-15), 2.0 x HDMI - 19 pin HDMI Type A, 1.0 x VGA output - RCA phono x 2, 1.0 x Composite video input - 9 pin D-Sub (DB-9), 1.0 x VGA input - 4 pin mini-DIN, 2.0 x S-video input - Mini-phone 3.5 mm, 1.0 x Audio line-in - 15 pin HD D-Sub (HD-15), 1.0 x Audio line-in - RJ-45

Operation

- **Lamp Type** 230.0 Watt

- **Lamp Life Cycle** 2500.0 hour(s) / 4000.0 hour(s) (economic mode)
- **Power Device** Power supply - Internal
- **Voltage Required** AC 120/230 V (50/60 Hz)
- **Max operating temperature** 95.0 °F
- **Min operating temperature** 41.0 °F
- **Sound emission** 36.0 dBA
- **Sound Emission (economic mode)** 31 dBA

Included accessories

- **Projector accessories** Wireless remote control
- **Mounting kit** Included

Miscellaneous

- **Security Features** Security lock slot (cable lock sold separately)

Manufacturer Warranty

- **Service & Support** 3 years warranty
- **Service & Support Details** Limited warranty - 3 years

