

# JABRA SPEAK™ 510

*Bluetooth*® and USB speakerphone  
Works with any *Bluetooth* enabled device



- Set up a conference call in seconds
- Conference calls via Bluetooth and USB connection
- Great sound for calls and streaming multimedia



FEATURE	BENEFIT
---------	---------

What is <i>Bluetooth</i> ® wireless technology?	<i>Bluetooth</i> wireless technology is a radio technology developed to deliver short-range wireless mobility. <i>Bluetooth</i> technology eliminates wires between devices, such as mobile phones and headsets, and enables communication between devices that are in close proximity to one another. <i>Bluetooth</i> facilitates fast, secure transmissions of both voice and data. More information is available at <a href="http://www.bluetooth.com">www.bluetooth.com</a> or <a href="http://www.bluetooth.org">www.bluetooth.org</a>
<i>Bluetooth</i> compliance	<i>Bluetooth</i> version 3.0
Supported <i>Bluetooth</i> profiles	A2DP (v1.2), hands free profile (v1.6), headset profile (v1.2), AGHFP (v1.6)
Compatibility	<i>Bluetooth</i> devices with <i>Bluetooth</i> 3.0 (or lower), works with: Microsoft, Skype, Cisco and other leading sofphone platforms. For the latest compatibility information, please visit <a href="http://www.jabra.com/pcsuite">www.jabra.com/pcsuite</a>
Supported modes	SCO, eSCO, sniff mode
Operating range	Up to 100 meters (up to 300 feet) with other class 1 devices, e.g Jabra Link360
Paired devices	Up to 8 trusted devices
Computer Connection	USB 2.0
USB Cord length	900 mm (35.4 in)
Talk time	Up to 15 hours
Standby time	Over 200 days, automatic power off
Charging time	Approximately 2,5 hours via USB
Weight	195 g (6.9 Oz)
Dimensions, main unit	Ø 120 mm, H 33 mm (Ø 4.72 in, H 1.30 in)
Microphone	Type: 6 mm omnidirectional electret microphone, Frequency response: Wideband - response 150 Hz to 6.5 KHz, Distortion: < 3% at 120 dB SPL
Speaker	Type: 50 mm electrodynamic speaker with neodymium magnet, Frequency response: Wideband - Response from 250 Hz to 10 KHz, Sensitivity: Output sensitivity in max volume: 0dB Pa/Vd Maximum output: Max SPL 250 Hz - 6500 Hz: 87 dB SPL @ 0.5m distance
Jack Port	Microphone load impedance: 3.3 kΩ, Receiver generator impedance: 300 Ω
Headset Port	3.5 mm (0.12 in) Stereo Jack for headset
Digital signal processing (DSP)	Noise reduction on transmit, build-in echo cancellar, Jabra loudness boost on receive
Operating temperature	5° C to 40° C (41 F to 104 F)
Storage temperature	-20° C to 45° C (-4 F to 113 F)
Jabra Speak™ 510 materials	Polycarbonate/acryl butadien styres (PC/ABS), polycarbonate (PC), thermoplastic elastomer (TPE)
Pairing passkey or PIN	0000
OS Compatibility	Win XP/SP3, Win7 64bit, Win7 32bit, MAC OS 10.6 and later. Works as audio device only (no call control)
Features	<i>Bluetooth</i> connection to: Mobile devices, headset and PC via Jabra Link360 <i>Bluetooth</i> USB adapter. Call control via USB and <i>Bluetooth</i> : Answer/End call, Call waiting, Reject call, Mute/un-mute, Volume up/down. On/off button. Battery indicator. Multimedia streaming. HD voice. Voice guidance.
What's in the box?	1 Jabra Speak™ 510 speakerphone, 1 Travel case, 1 quick start guide, 1 warning leaflet, 1 Warranty leaflet and 1 register paper.
Certification	RoHS, Reach, UL, CE, FCC, IC, SRRC (China), GOST (Russia), ACMA (Australia), Radcomms EMC (New Zealand), TELEC (Japan), KCC (South Korea), SIRIM (Malaysia), NTC (Philippines), NCC (Taiwan), IDA (Singapore), DGPosTel ( Indonesia), ETA (India)
Warranty	One-year limited warranty

